City of Escondido PRIORITY DEVELOPMENT PROJECT (PDP) SWQMP

[INSERT PROJECT NAME]
[INSERT RECORD ID (PERMIT) NUMBERS]

[INSERT PROJECT ADDRESS]
[INSERT PROJECT CITY, STATE ZIP CODE]

ASSESSOR'S PARCEL NUMBER(S): [INSERT APN(S)]

ENGINEER OF WORK:

[INSERT CIVIL ENGINEER'S NAME AND PE NUMBER HERE, PROVIDE WET SIGNATURE AND STAMP ABOVE LINE]

PREPARED FOR:

[INSERT APPLICANT NAME]
[INSERT ADDRESS]
[INSERT CITY, STATE ZIP CODE]
[INSERT TELEPHONE NUMBER]

PDP SWQMP PREPARED BY:

[INSERT COMPANY NAME]
[INSERT ADDRESS]
[INSERT CITY, STATE ZIP CODE]
[INSERT TELEPHONE NUMBER]

DATE OF SWQMP: [INSERT MONTH, DAY, YEAR]

PLANS PREPARED BY:
[INSERT CIVIL ENGINEER OR ARCHITECT]
[INSERT ADDRESS]
[INSERT CITY, STATE ZIP CODE]
[INSERT TELEPHONE NUMBER]

SWQMP APPROVED BY: [FOR CITY STAFF ONLY]

APPROVAL DATE:



This page was left intentionally blank.

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP] PDP SWQMP

TABLE OF CONTENTS

TABLE OF C	ONTENTS	iii
ATTACHMEN	NTS	iv
ACRONYMS		iv
PDP SWQMF	P PREPARER'S CERTIFICATION PAGE	v
SUBMITTAL	RECORD	vii
PROJECT VI	CINITY MAP	viii
Step 1: Pi	roject type determination (Standard or Priority Development Project) (Form I-2	²a) 1
Step 1.1:	Storm Water Quality Management Plan requirements	4
Step 1.2:	Exception to PDP definitions	4
Step 2: C	onstruction Storm Water BMPs	5
Step 3: C	ty of Escondido PDP SWQMP Site Information Checklist (Form I-2a)	6
Step 3.1:	Description of Existing Site Condition	6
Step 3.2:	Description of Existing Site Drainage Patterns	7
Step 3.3:	Description of Proposed Site Development	8
Step 3.4:	Description of Proposed Site Drainage Patterns	9
Step 3.5:	Potential Pollutant Source Areas	10
Step 3.6:	Identification and Narrative of Receiving Water and Pollutants of Concern .	11
Step 3.7:	Hydromodification Management Requirements	12
Step 3.7	1: Critical Coarse Sediment Yield Areas*	13
Step 3.7	2: Flow Control for Post-Project Runoff*	14
Step 3.8:	Other Site Requirements and Constraints	15
Step 4: So	ource Control BMP Checklist (Form I-2b)	16
Step 5: Si	te Design BMP Checklist (Form I-2c)	18
Step 6: Pl	DP Structural BMPs (Form I-3)	20
Step 6.1:	Description of structural BMP strategy	20
Step 6.2:	Structural BMP Checklist	22
Step 6.3	Offsite Alternative Compliance Participation Form	23

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
iii

ATTACHMENTS

Attachment 1: Backup for PDP Pollutant Control BMPs

Attachment 1a: Storm Water Pollutant Control Worksheet Calculations (Worksheet B.2-1

DCV, Form I-4)

Attachment 1b: Form I-5, Categorization of Infiltration Feasibility Condition

Attachment 1c: Form I-6, Factor of Safety and Design Infiltration Rate Worksheet

Attachment 1d: Drainage Management Area (DMA) Exhibit Attachment 1e: Individual Structural BMP DMA Mapbook

Attachment 2: Backup for PDP Hydromodification Control Measures

Attachment 2a: Flow Control Facility Design

Attachment 2b: Hydromodification Management Exhibit

Attachment 2c: Management of Critical Coarse Sediment Yield Areas Attachment 2d: Geomorphic Assessment of Receiving Channels (optional)

Attachment 2e: Vector Control Plan (if applicable)

Attachment 3: Structural BMP Maintenance Plan

Attachment 3a: Structural BMP Maintenance Thresholds and Actions

Attachment 3b: Draft Maintenance Agreements / Notifications (when applicable)

Attachment 4: City of Escondido PDP Structural BMP Verification

Attachment 5: Copy of Plan Sheets Showing Permanent Storm Water BMPs

ACRONYMS

ACP Alternative Compliance Project
APN Assessor's Parcel Number
BMP Best Management Practice
DMA Drainage Management Area

EOW Engineer of Work

HMP Hydromodification Management Plan

HSG Hydrologic Soil Group

MS4 Municipal Separate Storm Sewer System

N/A Not Applicable

PDP Priority Development Project
PE Professional Engineer

SC Source Control SD Site Design

SDRWQCB San Diego Regional Water Quality Control Board

SIC Standard Industrial Classification SWDM Storm Water Design Manual

SWQMP Storm Water Quality Management Plan WMAA Watershed Management Area Analysis

WQIP Water Quality Improvement Plan

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

iv

PDP SWQMP PREPARER'S CERTIFICATION PAGE

Project Name: [Insert Project Name]

Permit Application Number: [Insert Permit Application Number]

PREPARER'S CERTIFICATION

I hereby declare that I am the Engineer in Responsible Charge of design of storm water best management practices (BMPs) for this project, and that I have exercised responsible charge over the design of the BMPs as defined in Section 6703 of the Business and Professions Code, and that the design is consistent with the PDP requirements of the City of Escondido Storm Water Design Manual, which is a design manual for compliance with the City of Escondido Municipal Code (Chapter 22, Article 2) and regional MS4 Permit (California Regional Water Quality Control Board San Diego Region Order No. R9-2013-0001 as amended by R9-2015-0001 and R9-2015-0100) requirements for storm water management.

I have read and understand that the City of Escondido has adopted minimum requirements for managing urban runoff, including storm water, from land development activities, as described in the Storm Water Design Manual. I certify that this PDP SWQMP has been completed to the best of my ability and accurately reflects the project being proposed and the applicable BMPs proposed to minimize the potentially negative impacts of this project's land development activities on water quality. I understand and acknowledge that the plan check review of this PDP SWQMP by City staff is confined to a review and does not relieve me, as the Engineer in Responsible Charge of design of storm water BMPs for this project, of my responsibilities for project design.

Engineer of Work's Signature, PE Number & Expiration Date					
Print Name					
0					
Company					
Date	— Engineer's Seal:				

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

PDP SWQMP

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

PDP SWQMP vi

SUBMITTAL RECORD

Use this Table to keep a record of submittals of this PDP SWQMP. Each time the PDP SWQMP is re-submitted, provide the date and status of the project. In column 4 summarize the changes that have been made or indicate if response to plancheck comments is included. When applicable, insert response to plancheck comments behind this page.

Preliminary Design / Planning / CEQA

Submittal		
Number		
1		Initial Submittal
2		
3		
4		

Final Design

Submittal Number	Date	Summary of Changes
1		Initial Submittal
2		
3		
4		

Plan Changes

Submittal Number	Date	Summary of Changes
1		Initial Submittal
2		
3		
4		

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

vii

PROJECT VICINITY MAP

Project Name: [Insert Project Name]

Record ID: [Insert Record ID or Permit Application Number]

[Insert Project Vicinity Map here]

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

PDP SWQMP viii

Step 1: Project type determination (Standard or Priority Development Project) (Form I-2a)

Project Summary Information			
Project Name			
Project Address			
Assessor's Parcel Number(s)			
Permit Application Number			
Project Watershed (Hydrologic Unit)	Select One:		
	☐ Carlsbad 904	ne.	
Doroel Area	☐ San Dieguito 90	J3	
Parcel Area	Acres	(_ Square Feet)
(total area of Assessor's Parcel(s) associated with the project)		,	
Area to be disturbed by the project		,	
(Project Area)	Acres	(_ Square Feet)
Project Proposed Impervious Area	A	,	0
(subset of Project Area)	Acres	(_ Square Feet)
Project Proposed Pervious Area	A	,	0
(subset of Project Area)	Acres	(Square Feet)
Note: Proposed Impervious Area + Proposed Perv	ious Area = Area to	be Disturbed b	y the Project.
This may be less than the Parcel Area.			
Confirmation of Priority Dev	elopment Projec	t Determinati	ion
The project is (select one): ☐ New Development	☐ Redevelopment	t ¹	
The total proposed newly created or replaced impe	rvious area is:	ft ²	

Solar energy farms that are not also one of the categories listed in Step 2b of Table 1-1. City staff must also determine that appropriate BMPs are provided to mitigate for downstream impacts due to significant changes to the existing hydrology

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

1 of 42

¹ Redevelopment is defined as: The creation and/or replacement of impervious surface on an already developed site. Examples include the expansion of a building footprint, road widening, the addition to or replacement of a structure, and creation or addition of impervious surfaces. Replacement of impervious surfaces includes any activity that is not part of a routine maintenance activity where impervious material(s) are removed, exposing underlying soil during construction. Redevelopment does not include routine maintenance activities, such as trenching and resurfacing associated with utility work; pavement grinding; resurfacing existing roadways; new sidewalks construction; pedestrian ramps; or bike lanes on existing roads; and routine replacement of damaged pavement, such as pothole repair.

Is the	projec	t in ar	ny of the following categories, (a) through (f)?
Yes	No	(a)	New development projects that create 10,000 square feet or more of impervious surfaces (collectively over the entire project site). This includes commercial, industrial, residential, mixed-use, and public development projects on public or private land.
Yes	No 🗆	(b)	Redevelopment projects that create and/or replace 5,000 square feet or more of impervious surface (collectively over the entire project site on an existing site of 10,000 square feet or more of impervious surfaces). This includes commercial, industrial, residential, mixed-use, and public development projects on public or private land.
Yes	No	(c)	New and redevelopment projects that create and/or replace 5,000 square feet or more of impervious surface (collectively over the entire project site), and support one or more of the following uses: (i) Restaurants. This category is defined as a facility that sells prepared foods and drinks for consumption, including stationary lunch counters and refreshment stands selling prepared foods and drinks for immediate consumption (Standard Industrial Classification (SIC) code 5812). (ii) Hillside development projects. This category includes development on any natural slope that is twenty-five percent or greater. (iii) Parking lots. This category is defined as a land area or facility for the temporary parking or storage of motor vehicles used personally, for business, or for commerce. (iv) Streets, roads, highways, freeways, and driveways. This category is defined as any paved impervious surface used for the transportation of automobiles, trucks, motorcycles, and other vehicles.
Yes	No 🗆	(d)	New or redevelopment projects that create and/or replace 2,500 square feet or more of impervious surface (collectively over the entire project site), and discharging directly to an Environmentally Sensitive Area (ESA). "Discharging directly to" includes flow that is conveyed overland a distance of 200 feet or less from the project to the ESA, or conveyed in a pipe or open channel any distance as an isolated flow from the project to the ESA (i.e. not commingled with flows from adjacent lands). Note: ESAs are areas that include but are not limited to all Clean Water Act Section 303(d) impaired water bodies; areas designated as Areas of Special Biological Significance by the State Water Board and San Diego Water Board; State Water Quality Protected Areas; water bodies designated with the RARE beneficial use by the State Water Board and San Diego Water Board; and any other equivalent environmentally sensitive areas which have been identified by the Copermittees.
Yes	No	(e)	New development projects, or redevelopment projects that create and/or replace 5,000 square feet or more of impervious surface, that support one or more of the following uses: (i) Automotive repair shops. This category is defined as a facility that is categorized in any one of the following SIC codes: 5013, 5014, 5541, 7532-7534, or 7536-7539. (ii) Retail gasoline outlets (RGOs). This category includes RGOs that meet the following criteria: (a) 5,000 square feet or more or (b) a projected Average Daily Traffic (ADT) of 100 or more vehicles per day.

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP
2 of 42

Yes	No	(e)	New development projects, or redevelopment projects that create and/or replace 5,000 square feet or more of impervious surface, that support one or more of the following uses:
			(iii) Automotive repair shops. This category is defined as a facility that is
			categorized in any one of the following SIC codes: 5013, 5014, 5541, 7532-7534, or 7536-7539.
			(iv) Retail gasoline outlets (RGOs). This category includes RGOs that meet the
			following criteria: (a) 5,000 square feet or more or (b) a projected Average
			Daily Traffic (ADT) of 100 or more vehicles per day.
Yes	No	(f)	New or redevelopment projects that result in the disturbance of one or more acres
			of land and are expected to generate pollutants post construction.
			Note: See Storm Water Design Manual Section 1.4.2 for additional guidance.
☐ N	es – the	proje e proje ce may	ct is <u>not</u> a Priority Development Project (Standard Project). ect is a Priority Development Project (PDP). be found in Chapter 1 and Table 1-2 of the Storm Water Design Manual. or redevelopment PDPs only:
The to Perce	otal pro ent imp percent less	pose erviou impe than	ng (pre-project) impervious area at the project site is: d newly created or replaced impervious area is s surface created or replaced (B/A)*100: rvious surface created or replaced is (select one based on the above calculation): or equal to fifty percent (50%) – only newly created or replaced impervious areas sidered a PDP and subject to stormwater requirements
	OR	30.10	and the second s
	□ grea	ater th	an fifty percent (50%) - the entire project site is considered a PDP and subject to
	sto	rmwa	ater requirements

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP 3 of 42

Step 1.1: Storm Water Quality Management Plan requirements

Step	Answer	Progression
Is the project a Standard Project,	□ Standard	Standard Project requirements apply, including
Priority Development Project (PDP), or	Project	Standard Project SWQMP.
exception to PDP definitions?		Complete Form I-1.
To answer this item, complete Step 1	□ PDP	Standard and PDP requirements apply,
Project Type Determination Checklist		including PDP SWQMP.
on Pages 1 and 2, and see PDP exemption information below.		SWQMP Required.
For further guidance, see Section 1.4	☐ PDP with	If participating in offsite alternative compliance,
of the Storm Water Design Manual in	ACP	complete Step 6.3 and an ACP SWQMP.
its entirety.	,	
	□ PDP	Go to Step 1.2 below.
	Exemption	

Step 1.2: Exemption to PDP definitions

Is the project exempt from PDP definitions based on either of the following:	If so:
 Projects that are only new or retrofit paved sidewalks, bicycle lanes, or trails that meet the following criteria: Designed and constructed to direct storm water runoff to adjacent vegetated areas, or other non-erodible permeable areas; OR Designed and constructed to be hydraulically disconnected from paved streets or roads [i.e., runoff from the new improvement does not drain directly onto paved streets or roads]; OR Designed and constructed with permeable pavements or surfaces in accordance with County of San Diego Green Streets Infrastructure; 	Standard Project requirements apply, AND any additional requirements specific to the type of project. City concurrence with the exemption is required. Provide discussion and list any additional requirements below in this form.
☐ Projects that are only retrofitting or redeveloping existing paved alleys, streets or roads that are designed and constructed in accordance with the City of Escondido Guidance on Green Infrastructure.	PDP Exempt.
Discussion / justification, and additional requirements for exceptions to PDP	definitions, if applicable:

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

4 of 42

Step 2: Construction Storm Water BMPs

Construction storm water BMPs shall be shown on the Grading Plan and (if applicable) included in the Storm Water Pollution Prevention Plan (SWPPP).

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

PDP SWQMP

5 of 42

Step 3: City of Escondido PDP SWQMP Site Information Checklist (Form I-2a)

Step 3.1: Description of Existing Site Condition

Current Status of the Site (select all that apply):
☐Existing development
□Previously graded but not built out
☐Demolition completed without new construction
□Agricultural or other non-impervious use
□Vacant, undeveloped/natural
Description / Additional Information
Description / Additional Information:
Existing Land Cover Includes (select all that apply and provide each area on site):
□Vegetative Cover Acres (Square Feet)
□Non-Vegetated Pervious Areas Acres (Square Feet)
□Impervious Areas Acres (Square Feet)
Description / Additional Information:
Underlying Soil belongs to Hydrologic Soil Group (select all that apply):
□NRCS Type A
□NRCS Type B
□NRCS Type C
□NRCS Type D
Approximate Depth to Groundwater (GW) (or N/A for no infiltration BMPs):
□GW Depth < 5 feet
□5 feet < GW Depth < 10 feet
□10 feet < GW Depth < 20 feet
□GW Depth > 20 feet
Existing Natural Hydrologic Features (select all that apply):
□Watercourses
□Seeps
□Springs
□Wetlands
□None
□Other
Description / Additional Information:

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP
6 of 42

Step 3.2: Description of Existing Site Drainage Patterns

How is storm water runoff conveyed from the site? At a minimum, this description should answer:

- (1) Whether existing drainage conveyance is natural or urban;
- (2) Is runoff from offsite conveyed through the site? if yes, quantify all offsite drainage areas, design flows, and locations where offsite flows enter the project site, and summarize how such flows are conveyed through the site;
- (3) Provide details regarding existing project site drainage conveyance network, including any existing storm drains, concrete channels, swales, detention facilities, storm water treatment facilities, natural or constructed channels; and
- (4) Identify all discharge locations from the existing project site along with a summary of conveyance system size and capacity for each of the discharge locations. Provide summary of the pre-project drainage areas and design flows to each of the existing runoff discharge locations.

Describe existing site drainage patterns:			

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

7 of 42

Step 3.3: Description of Proposed Site Development

District Description / Disposed Land Has and/or Activities
Project Description / Proposed Land Use and/or Activities:
List/describe proposed impervious features of the project (e.g., buildings, roadways, parking lots, courtyards, athletic courts, other impervious features):
,
List/describe proposed pervious features of the project (e.g., landscape areas):
Does the project include grading and changes to site topography?
□Yes
□No
Description / Additional Information:

Insert acreage or square feet for the different land cover types in the table below:

Change in Land Cover Type Summary				
Land Cover Type	Existing	Proposed	Percent	
	(acres or ft ²)	(acres or ft ²)	Change	
Vegetation				
Pervious (non-vegetated)				
Impervious				

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

8 of 42

Step 3.4: Description of Proposed Site Drainage Patterns

Does the project include changes to site drainage (e.g., installation of new storm water
conveyance systems)?
□Yes
□No
If yes, provide details regarding the proposed project site drainage conveyance network, including storm drains, concrete channels, swales, detention facilities, storm water treatment facilities, natural or constructed channels, and the method for conveying offsite flows through or around the proposed project site. Identify all discharge locations from the proposed project site along with a summary of the conveyance system size and capacity for each of the discharge locations. Provide a summary of pre- and post-project drainage areas and design flows to each of the runoff discharge locations. Reference the drainage study for detailed calculations.
Describe proposed site drainage patterns:

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

PDP SWQMP 9 of 42

Step 3.5: Potential Pollutant Source Areas

Identify whether any of the following features, activities, and/or pollutant source areas will be present (select all that apply).
□ On-site storm drain inlets □ Interior floor drains and elevator shaft sump pumps □ Interior parking garages □ Need for future indoor & structural pest control □ Landscape/Outdoor Pesticide Use □ Pools, spas, ponds, decorative fountains, and other water features □ Food service □ Refuse areas □ Industrial processes □ Outdoor storage of equipment or materials □ Vehicle and Equipment Cleaning □ Vehicle/Equipment Repair and Maintenance □ Fuel Dispensing Areas □ Loading Docks □ Fire Sprinkler Test Water □ Miscellaneous Drain or Wash Water □ Plazas, sidewalks, and parking lots □ Other (provide description)
Description / Additional Information:

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP
10 of 42

Step 3.6: Identification and Narrative of Receiving Water and Pollutants of Concern

Describe flow path of storm water from the project site discharge location(s), through urban storm conveyance systems as applicable, to receiving creeks, rivers, and lagoons as applicable, and ultimate discharge to the Pacific Ocean (or bay, lagoon, lake or reservoir, as applicable):

List any 303(d) impaired water bodies² within the path of storm water from the project site to the Pacific Ocean (or bay, lagoon, lake or reservoir, as applicable), identify the pollutant(s)/stressor(s) causing impairment, and identify any TMDLs and/or Highest Priority Pollutants from the WQIP for the impaired water bodies:

303(d) Impaired Water Body	Pollutant(s)/Stressor(s)	TMDLs / WQIP Highest Priority Pollutant

Identification of Project Site Pollutants*

Identify pollutants expected from the project site based on all proposed use(s) of the site (see Storm Water Design Manual Appendix B.6):

Pollutant	Not Applicable to the Project Site	Anticipated from the Project Site	Also a Receiving Water Pollutant of Concern
Sediment			
Nutrients			
Heavy Metals			
Organic Compounds			
Trash & Debris			
Oxygen Demanding Substances			
Oil & Grease			
Bacteria & Viruses			
Pesticides			

² The current list of Section 303(d) impaired water bodies can be found at http://www.waterboards.ca.gov/water_issues/programs/water_quality_assessment/#impaired

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP 11 of 42

^{*}Identification of project site pollutants below is only required if flow-thru treatment BMPs are implemented onsite in lieu of retention or biofiltration BMPs. Note the project must also participate in an alternative compliance program (unless prior lawful approval to meet earlier PDP requirements is demonstrated).

Step 3.7: Hydromodification Management Requirements

Do business difference of the Charge Water				
Do hydromodification management requirements apply (see Section 1.6 of the Storm Water				
Design Manual)?				
☐Yes, hydromodification management requirements for flow control and preservation of critical				
coarse sediment yield areas are applicable.				
\square No, the project will discharge runoff directly to existing underground storm drains discharge				
directly to water storage reservoirs, lakes, enclosed embayments, or the Pacific Ocean.				
\square No, the project will discharge runoff directly to conveyance channels whose bed and bank are				
concrete-lined all the way from the point of discharge to water storage reservoirs, lakes,				
enclosed embayments, or the Pacific Ocean.				
□No, the project will discharge runoff directly to an area identified as appropriate for an				
exemption by the WMAA ³ for the watershed in which the project resides.				
Description / Additional Information (to be provided if a 'No' answer has been selected above):				

http://www.projectcleanwater.org/index.php?option=com_content&view=article&id=248

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP
12 of 42

³The Watershed Management Area Analysis (WMAA) is an optional element for inclusion in the Water Quality Improvement Plans (WQIPs) described in the 2013 MS4 Permit [Provision B.3.b.(4)]. It is available online at the Project Clean Water website:

Step 3.7.1: Critical Coarse Sediment Yield Areas*

otop offit. Officer obtained their Arcas
*This Section only required if hydromodification management requirements apply
Based on the maps provided within the WMAA, do potential critical coarse sediment yield areas exist within the project drainage boundaries? □ Yes
□ No, no critical coarse sediment yield areas to be protected based on WMAA maps
If yes, have any of the optional analyses presented in Section 6.2 of the manual been performed? □ 6.2.1 Verification of GLUs (classification that provides an estimate of sediment yield based on
geology, hillslope, and land cover) Onsite □ 6.2.2 Downstream Systems Sensitivity to Coarse Sediment
 □ 6.2.3 Optional Additional Analysis of Potential Critical Coarse Sediment Yield Areas Onsite □ No optional analyses performed, the project will avoid critical coarse sediment yield areas identified based on WMAA maps
If optional analyses were performed, what is the final result? □ No critical coarse sediment yield areas to be protected based on verification of GLUs onsite. □ Critical coarse sediment yield areas exist but additional analysis has determined that protection is not required. Documentation attached in Attachment 8 of the SWQMP. □ Critical coarse sediment yield areas exist and require protection. The project will implement management measures described in Sections 6.2.4 and 6.2.5 as applicable, and the areas are identified on the SWQMP Exhibit.
Discussion / Additional Information:

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP
13 of 42

Flow Control for Post-Project Runoff*

*This Section only required if hydromodification management requirements apply			
List and describe point(s) of compliance (POCs) for flow control for hydromodification			
management (see Section 6.3.1). For each POC, provide a POC identification name or number			
correlating to the project's HMP Exhibit and a receiving channel identification name or number			
correlating to the project's HMP Exhibit.			
Has a geomorphic assessment been performed for the receiving channel(s)?			
□No, the low flow threshold is 0.1Q2 (default low flow threshold)			
☐Yes, the result is the low flow threshold is 0.1Q2			
☐Yes, the result is the low flow threshold is 0.3Q2			
☐Yes, the result is the low flow threshold is 0.5Q2			
If a geomorphic assessment has been performed, provide title, date, and preparer:			
Discussion / Additional Information: (optional)			

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP
14 of 42

Step 3.8: Other Site Requirements and Constraints

When applicable, list other site requirements or constraints that will influence storm water management design, such as zoning requirements including setbacks and open space, or local codes governing minimum street width, sidewalk construction, allowable pavement types, and drainage requirements.

Ontional Additional Information or Continuation of Bravious Sections As Needed					
Optional Additional Information or Continuation of Previous Sections As Needed This space provided for additional information or continuation of information from previous					
sections as needed.					

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP
15 of 42

Step 4:	Source Control BMP Checklist (Form I	-2b)		
	Source Control BMPs			
All development projects must implement source control BMPs 4.2.1 through 4.2.6 where applicable and feasible. See Chapter 4.2 and Appendix E of the City Storm Water Design Manual for information to implement source control BMPs shown in this checklist. The following checklists serve as guides only. Mark what elements are included in your project. See Storm Water Design Manual Chapter 4 and Appendix E for more information on determining appropriate BMPs for your project.				
Answer each category below pursuant to the following: • "Yes" means the project will implement the source control BMP as described in Chapter 4.2 and/or Appendix E of the City Storm Water Design Manual. Discussion / justification is not required.				
	means the BMP is applicable to the project but it is no	ot feasible	to implem	ent.
 Discussion / justification must be provided. "N/A" means the BMP is not applicable at the project site because the project does not include the feature that is addressed by the BMP (e.g., the project has no outdoor materials storage areas). Discussion / justification must be provided. 				
	Source Control Requirement		Applied?)
	ntion of Illicit Discharges into the MS4	□Yes	□No	□N/A
 □ Direct irrigation water away from impervious surfaces □ Direct vehicle wash water away from impervious surfaces □ Other:				
SC-2 Storm	Drain Stenciling or Signage	□Yes	□No	□N/A
□ Ster	ncil or stamp storm drains with anti-dumping message t signs prohibiting illegal dumping			
Discussion / justification if SC-2 not implemented:				
Run-On, Ru	ct Outdoor Materials Storage Areas from Rainfall, unoff, and Wind Dispersal	□Yes	□No	□N/A
	e materials inside a covered enclosure ct runoff from downspouts and roofs away from storag er	e areas		
Discussion / justification if SC-3 not implemented:				

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP] PDP SWQMP 16 of 42

SC-4 Protect Materials Stored in Outdoor Work Areas from Rainfall, Run-On, Runoff, and Wind Dispersal	□Yes	□No	□N/A
□ Locate work area away from storm drains or catch basins Work over impermeable surfaces where spills and pollutants can be captured and removed			
Discussion / justification if SC-4 not implemented:			
SC-5 Protect Trash Storage Areas from Rainfall, Run-On, Runoff, and Wind Dispersal	□Yes	□No	□N/A
□ Locate trash containers in a roofed, walled enclosure □ Locate trash containers away from storm drains Discussion / justification if SC-5 not implemented:			
SC-6 Additional BMPs Based on Potential Sources of Runoff Pollutants (must answer for each source listed below):			
☐ A. On-site storm drain inlets	□Yes	□No	□N/A
☐ B. Interior floor drains and elevator shaft sump pumps	□Yes	□No	□N/A
☐ C. Interior parking garages	□Yes	□No	□N/A
☐ D. Need for future indoor & structural pest control	□Yes	□No	□N/A
☐ E. Landscape/outdoor pesticide use	□Yes	□No	□N/A
☐ F. Pools, spas, ponds, fountains, and other water features	□Yes	□No	□N/A
☐ G. Food service	□Yes	□No	□N/A
☐ H. Refuse areas	□Yes	□No	□N/A
☐ I. Industrial processes	□Yes	□No	□N/A
☐ J. Outdoor storage of equipment or materials	□Yes	□No	□N/A
☐ K. Vehicle and equipment cleaning	□Yes	□No	□N/A
☐ L. Vehicle/equipment repair and maintenance	□Yes	□No	□N/A
☐ M. Fuel dispensing areas	□Yes	□No	□N/A
□ N. Loading docks	□Yes	□No	□N/A
□ O. Fire sprinkler test water	□Yes	□No	□N/A
☐ P. Miscellaneous drain or wash water	□Yes	□No	□N/A
☐ Q. Plazas, sidewalks, and parking lots	□Yes	□No	⊠N/A
Discussion / justification if SC-6 not implemented. Clearly identify pollutants are discussed. Justification must be provided for <u>all</u> "No			

Note: Show all source control measures described above that are included in design capture volume calculations in the plan sheets of Attachment 5.

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP
17 of 42

Step 5: Site Design BMP Checklist (Form I-2c)

Site Design BMPs			
All development projects must implement site design BMPs SD-A through SD-H where applicable and feasible. See Chapter 4.3 and Appendix E of the City Storm Water Design Manual for information to implement site design BMPs shown in this checklist. The following checklists serve as guides only. Mark what elements are included in your project. See Storm Water Design Manual Chapter 4 and Appendix E for more information on determining appropriate BMPs for your project.			
 Answer each category below pursuant to the following: "Yes" means the project will implement the site design BMF and/or Appendix E of the City Storm Water Design Manual not required. "No" means the BMP is applicable to the project but it is not Discussion / justification must be provided. "N/A" means the BMP is not applicable at the project site be include the feature that is addressed by the BMP (e.g., the natural areas to conserve). Discussion / justification must be 	Discussion the discussion of t	on / justific to impleme e project d e has no e d.	ation is ent. loes not existing
Site Design Requirement		Applied?	
SD-1 Maintain Natural Drainage Pathways and Hydrologic Features	□Yes	□No	□N/A
 Maintain existing drainage patterns Discussion / justification if SD-1 not implemented: SD-2 Conserve Natural Areas, Soils, and Vegetation 	□Yes	□No	□N/A
 Preserve trees (see Zoning Code Art. 55 Grading & Erosion Regulations) Avoid sensitive areas such as wetlands and waterways 	n Control;	Art. 62 Lar	ndscape
Discussion / justification if SD-2 not implemented:			
SD-3 Minimize Impervious Area	□Yes	□No	□N/A
Install parking and driving aisles to minimum width required	d to meet s	standards	
Discussion / justification if SD-3 not implemented:			

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP
18 of 42

SD-4 Minimize Soil Compaction	□Yes	□No	□N/A
 Avoid compaction in planned landscaped spaces 			
□ Till and amend soil for improved infiltration capacity			
Discussion / justification if SD-4 not implemented:			
SD-5 Impervious Area Dispersion	□Yes	□No	□N/A
 Drain rooftops, roads or sidewalks into adjacent landscape 	areas	l	
□ Drain impervious surfaces through pervious areas			
Discussion / justification if SD-5 not implemented:			
SD-6 Runoff Collection		□Vos	
SD-6 Runoff Collection Discussion / Justification if SD 6 not implemented:	□Vaa	□Yes	□NI/A
SD-6 Runoff Collection Discussion / justification if SD-6 not implemented:	□Yes	□Yes	□N/A
	□Yes		□N/A
	□Yes		□N/A
Discussion / justification if SD-6 not implemented:	□Yes		□N/A
	□Yes		□N/A
Discussion / justification if SD-6 not implemented: SD-7 Landscaping with Native or Drought Tolerant Species		□No	
Discussion / justification if SD-6 not implemented: SD-7 Landscaping with Native or Drought Tolerant Species		□No	
Discussion / justification if SD-6 not implemented: SD-7 Landscaping with Native or Drought Tolerant Species Discussion / justification if SD-7 not implemented:		□No	
Discussion / justification if SD-6 not implemented: SD-7 Landscaping with Native or Drought Tolerant Species Discussion / justification if SD-7 not implemented: SD-8 Harvesting and Using Precipitation		□No	□N/A
Discussion / justification if SD-6 not implemented: SD-7 Landscaping with Native or Drought Tolerant Species Discussion / justification if SD-7 not implemented:		□No	
Discussion / justification if SD-6 not implemented: SD-7 Landscaping with Native or Drought Tolerant Species Discussion / justification if SD-7 not implemented: SD-8 Harvesting and Using Precipitation	□Yes	□No	□N/A
Discussion / justification if SD-6 not implemented: SD-7 Landscaping with Native or Drought Tolerant Species Discussion / justification if SD-7 not implemented: SD-8 Harvesting and Using Precipitation	□Yes	□No	□N/A

Note: Show all site design measures described above that are included in design capture volume calculations in the plan sheets of Attachment 5.

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP
19 of 42

Step 6: PDP Structural BMPs (Form I-3)

All PDPs must implement structural BMPs for storm water pollutant control (see Chapter 5 of the Storm Water Design Manual). Selection of PDP structural BMPs for storm water pollutant control must be based on the selection process described in Chapter 5. PDPs subject to hydromodification management requirements must also implement structural BMPs for flow control for hydromodification management (see Chapter 6 of the Storm Water Design Manual). Both storm water pollutant control and flow control for hydromodification management can be achieved within the same structural BMP(s).

PDP structural BMPs must be verified by the City at the completion of construction. This may include requiring the project owner or project owner's representative and engineer of record to certify construction of the structural BMPs (see Section 8.2.3.2 of the Storm Water Design Manual). PDP structural BMPs must be maintained into perpetuity, and the City must confirm the maintenance (see Section 7 of the Storm Water Design Manual).

Use this section to provide narrative description of the general strategy for structural BMP implementation at the project site in the box below. Then complete the PDP structural BMP summary information sheet (Step 6.2) for each structural BMP within the project (copy the BMP summary information sheet [Step 6.2] as many times as needed to provide summary information for each individual structural BMP).

Step 6.1: Description of structural BMP strategy

Describe the general strategy for structural BMP implementation at the site. This information must describe how the steps for selecting and designing storm water pollutant control BMPs presented in Section 5.1 of the Storm Water Design Manual were followed, and the results (t of BMPs selected). For projects requiring hydromodification flow control BMPs, indicate whet pollutant control and flow control BMPs are integrated or separate. At the end of this discuss provide a summary of all the structural BMPs within the project including the type and number of the structural based on the structural based	type ther ion
(Continue on following page as necessary.)	

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

PDP SWQMP

20 of 42

Description of structural BMP strategy continued (Page reserved for continuation of description of general strategy for structural BMP implementation at the site)		
(Continued from previous page)		

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP
21 of 42

Step 6.2: Structural BMP Checklist


(Copy this page as needed to provide information for each individual proposed structural BMP)		
Structural BMP ID No.		
Construction Plan Sheet No.		
Type of structural BMP:		
Retention by harvest and use (HU-1)		
□Retention by infiltration basin (INF-1)		
☐Retention by bioretention (INF-2)		
☐Retention by permeable pavement (INF-3)		
\square Partial retention by biofiltration with partial rete	ention (PR-1)	
☐Biofiltration (BF-1)		
☐Biofiltration with Nutrient Sensitive Media Des	ign (BF-2)	
☐ Proprietary Biofiltration (BF-3) meeting all req	• •	
☐Flow-thru treatment control with prior lawful applications.	·	
(provide BMP type/description in discussion s	•	
☐ Flow-thru treatment control included as pre-tre	· ·	
biofiltration BMP (provide BMP type/description biofiltration BMP it serves in discussion sections.)		
Flow-thru treatment control with alternative co	,	
discussion section below)	impliance (provide bivilitype/description in	
Detention pond or vault for hydromodification	management	
☐Other (describe in discussion section below)		
Purpose:		
☐Pollutant control only		
☐ Hydromodification control only		
☐ Combined pollutant control and hydromodification	ition control	
□ Pre-treatment/forebay for another structural BMP		
☐Other (describe in discussion section below)		
Who will certify construction of this BMP?		
Provide name and contact information for the		
party responsible to sign BMP verification forms (See Section 8.2.3.2 of the Storm Water		
Design Manual)		
Who will be the final owner of this BMP?	□HOA □Property Owner □City	
	□Other (describe)	
Who will maintain this BMP into perpetuity?	□HOA □Property Owner □City	
	□Other (describe)	
Discussion (as needed):	- (/	
(Continue on subsequent pages as necessary)		

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP
22 of 42

Step 6.3: Offsite Alternative Compliance Participation Form

THIS FORM IS NOT APPLICABLE AT THIS TIME: An Alternative Compliance Program is			
under consideration by the City of Escondido.			
PDP INFORMATION			
Record ID:			
Assessor's Parcel Number(s) [APN(s)]			
What are your PDP Pollutant Control Debits? *See Attachment 1 of the PDP SWQMP			
What are your PDP HMP Debits? (if applicable) *See Attachment 2 of the PDP SWQMP			
ACP Information			
Record ID:			
Assessor's Parcel Number(s) [APN(s)]			
Project Owner/Address			
What are your ACP Pollutant Control Credits? *See Attachment 1 of the ACP SWQMP			
What are your ACP HMP Debits? (if applicable) *See Attachment 2 of the ACP SWQMP			
Is your ACP in the same watershed as your PDP? ☐Yes ☐No	Will your ACP project be completed prior to the completion of the PDP? ☐Yes ☐No		
Does your ACP account for all Deficits generated by the PDP? Yes No (PDP and/or ACP must be redesigned to account for all deficits generated by the PDP.)	What is the difference between your PDP debits and ACP Credits? *(ACP Credits -Total PDP Debits = Total Earned Credits)		

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP
23 of 42



Template Date: October 2016 PDP SWQMP - Attachments

Preparation Date: [INSERT DATE OF SWQMP]

ATTACHMENT 1

BACKUP FOR PDP POLLUTANT CONTROL BMPS

This is the cover sheet for Attachment 1.

Indicate which Items are Included behind this cover sheet:

Attachment	Contents	Checklist
Sequence		
Attachment 1a	Storm Water Pollutant Control Worksheet Calculations -Worksheet B.2-1 (Required) -Worksheet B.3-1 (Form I-4; Required) -Worksheet B.4-1 (if applicable) -Worksheet B.5-1 (if applicable) -Worksheet B.5-2 (if applicable) -Worksheet B.5-3 (if applicable) -Worksheet B.6-1 (if applicable) -Summary Worksheet (optional)	□Included
Attachment 1b	Form I-5, Categorization of Infiltration Feasibility Condition (Required unless the project will use harvest and use BMPs) Refer to Appendices C and D of the Storm Water Design Manual to complete Form I-5.	☐ Included ☐ Not included because the entire project will use harvest and use BMPs
Attachment 1c	Form I-6, Factor of Safety and Design Infiltration Rate Worksheet (Required unless the project will use harvest and use BMPs) Refer to Appendices C and D of the Storm Water Design Manual to complete Form I-6.	☐ Included ☐ Not included because the entire project will use harvest and use BMPs
Attachment 1d	DMA Exhibit (Required) See DMA Exhibit Checklist on the back of this Attachment cover sheet.	□Included
Attachment 1e	Individual Structural BMP DMA Mapbook (Required) -Place each map on 8.5"x11" paperShow at a minimum the DMA, Structural BMP, and any existing hydrologic features within the DMA.	□Included

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]
PDP SWQMP - Attachments

This page was left intentionally blank.

Template Date: October 2016 PDP SWQMP - Attachments

Preparation Date: [INSERT DATE OF SWQMP]

Use this checklist to ensure the required information has been included on the DMA Exhibit:

The DMA Exhibit must identify:
☐Underlying hydrologic soil group
□ Approximate depth to groundwater
☐ Existing natural hydrologic features (watercourses, seeps, springs, wetlands)
☐Critical coarse sediment yield areas to be protected
□Existing topography and impervious areas
☐ Existing and proposed site drainage network and connections to drainage offsite
□ Proposed demolition
□ Proposed grading
□ Proposed impervious features
□ Proposed design features and surface treatments used to minimize imperviousness
□ Drainage management area (DMA) boundaries, DMA ID numbers, and DMA areas (square
footage or acreage), and DMA type (i.e., drains to BMP, self-retaining, or self-mitigating)
□Potential pollutant source areas and corresponding required source controls (see Chapter 4
Appendix E.1, and Step 3.5)
☐ Structural BMPs (identify location, structural BMP ID#, type of BMP, and size/detail)

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

PDP SWQMP - Attachments

Worksheet B.2-1. DCV

	Design Capture Volume	Worksheet B-2.1	
1	85 th percentile 24-hr storm depth from Figure B.1-1	d=	inches
2	Area tributary to BMP (s)	A=	acres
3	Area weighted runoff factor (estimate using Appendix B.1.1 and B.2.1)	C=	unitless
4	Street trees volume reduction	TCV=	cubic- feet
5	Rain barrels volume reduction	RCV=	cubic- feet
6	Calculate DCV = (3630 x C x d x A) – TCV - RCV	DCV=	cubic- feet

Template Date: October 2016 PDP SWQMP - Attachments

Categorization of Infiltration Feasibility Form I-5 Condition Part 1 - Full Infiltration Feasibility Screening Criteria Would infiltration of the full design volume be feasible from a physical perspective without any undesirable consequences that cannot be reasonably mitigated? Criteria Screening Question Yes No Is the estimated reliable infiltration rate below proposed facility locations greater than 0.5 inches per hour? The 1 response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.2 and Appendix D. Provide basis: Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability. Can infiltration greater than 0.5 inches per hour be allowed without increasing risk of geotechnical hazards (slope stability, groundwater mounding, utilities, or other factors) 2 that cannot be mitigated to an acceptable level? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.2. Provide basis: Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability.

Template Date: October 2016
PDP SWQMP - Attachments

	Form I-5		
Criteria	Screening Question	Yes	No
3	Can infiltration greater than 0.5 inches per hour be allowed without increasing risk of groundwater contamination (shallow water table, storm water pollutants or other factors) that cannot be mitigated to an acceptable level? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.		
Provide b	asis:		1
	ce findings of studies; provide reference to studies, calculations, maps, dan of study/data source applicability. Can infiltration greater than 0.5 inches per hour be allowed without causing potential water balance issues such as change of seasonality of ephemeral streams or increased discharge of contaminated groundwater to surface waters? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.	nta sources, etc.	Provide narrative
Provide b	7 77		
	ze findings of studies; provide reference to studies, calculations, maps, dan of study/data source applicability.	nta sources, etc.	Provide narrative
D 1	If all answers to rows 1 - 4 are " Yes " a full infiltration design is potent The feasibility screening category is Full Infiltration	cially feasible.	
Part 1 Result*	If any answer from row 1-4 is " No ", infiltration may be possible to so would not generally be feasible or desirable to achieve a "full infiltration Proceed to Part 2		

Template Date: October 2016 PDP SWQMP - Attachments

Form I-5 Part 2 – Partial Infiltration vs. No Infiltration Feasibility Screening Criteria Would infiltration of water in any appreciable amount be physically feasible without any negative consequences that cannot be reasonably mitigated? Criteria Screening Question Yes No Do soil and geologic conditions allow for infiltration in any appreciable rate or volume? The response to this Screening 5 Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.2 and Appendix D. Provide basis: Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability and why it was not feasible to mitigate low infiltration rates. Can Infiltration in any appreciable quantity be allowed without increasing risk of geotechnical hazards (slope stability, groundwater mounding, utilities, or other factors) 6 that cannot be mitigated to an acceptable level? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.2. Provide basis:

Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability and why it was not feasible to mitigate low infiltration rates.

Template Date: October 2016
PDP SWQMP - Attachments

	Form I-5		
Criteria	Screening Question	Yes	No
7	Can Infiltration in any appreciable quantity be allowed without posing significant risk for groundwater related concerns (shallow water table, storm water pollutants or other factors)? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.		
Provide b	asis:		
	the findings of studies; provide reference to studies, calculations, maps, date of study/data source applicability and why it was not feasible to mitigate		
8	Can infiltration be allowed without violating downstream water rights? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.		
	water rights? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.		
	water rights? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.		
8 Provide b	water rights? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.		
Provide b	water rights? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.		
Provide b	water rights? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3. asis: te findings of studies; provide reference to studies, calculations, maps, days to the factors presented in Appendix C.3.	te low infiltration r	

Template Date: October 2016 PDP SWQMP - Attachments

Form I-5 Certification

The Geotechnical Engineer certifies they completed Form I-5 except Criteria 4 & 8 (see Appendix C.4.3).

Professional Geotechnical Engineer's Printed Name:	[SEAL]
Professional Geotechnical Engineer's Signed Name:	
Date:	
The Project Design Engineer certifies they completed C	riteria 4 & 8 (see Appendix C.4.4)
Professional Project Design Engineer's Printed Name:	[SEAL]
Professional Project Design Engineer's Signed Name:	
Date:	

This page was left intentionally blank.

Template Date: October 2016 PDP SWQMP - Attachments

	Facto	r of Safety and Design Infilt	ration Rate Worksheet	For	rm I-6
Fac	ctor Category	Factor Description	Assigned Weight (w)	Factor Value (v)	Product (p) $p = w \times v$
		Soil assessment methods	0.25		
		Predominant soil texture	0.25		
Α	Suitability	Site soil variability	0.25		
Λ	Assessment	Depth to groundwater / impervious layer	0.25		
		Suitability Assessment Safety Fact	or, $S_A = \Sigma p$		
	Design	Level of pretreatment/ expected sediment loads	0.5		
В		Redundancy/resiliency	0.25		
İ		Compaction during construction	0.25		
		Design Safety Factor, $S_B = \Sigma p$			
Combined Safety Factor, $S_{total} = S_A \times S_B$					
Observed Infiltration Rate, inch/hr, K _{observed} (corrected for test-specific bias)					
Desi	gn Infiltration I	Rate, in/hr, $K_{design} = K_{observed} / S_{total}$			
Supporting Data					
Briefly describe infiltration test and provide reference to test forms:					

Factor of Safety and Design Infiltration Rate Worksheet

Form I-6 Certification

The Geotechnical Engineer certifies they completed Form I-6 (see Appendix C.4.3).

Professional Geotechnical Engineer's Printed Name:	[SEAL]
Professional Geotechnical Engineer's Signed Name:	
Date:	

ATTACHMENT 2

BACKUP FOR PDP HYDROMODIFICATION CONTROL MEASURES

This is the cover sheet for Attachment 2.

☐ Mark this box if this attachment is empty because the project is exempt from PDP hydromodification management requirements.

Indicate which Items are Included behind this cover sheet:

Attachment Sequence	Contents	Checklist
Attachment 2a	Flow Control Facility Design, including Structural BMP Drawdown Calculations and Overflow Design Summary (Required) See Chapter 6 and Appendix G of the Storm Water Design Manual	☐ Included ☐ Submitted as separate standalone document
Attachment 2b	Hydromodification Management Exhibit (Required)	□Included See Hydromodification Management Exhibit Checklist on the back of this Attachment cover sheet.
Attachment 2c	Management of Critical Coarse Sediment Yield Areas See Section 6.2 and Appendix H of the Storm Water Design Manual.	□ Exhibit depicting onsite and/or upstream sources of critical coarse sediment as mapped in the WMAA AND, □ Demonstration that the project effectively avoids and bypasses sources of mapped critical coarse sediment OR, □ Demonstration that project does not generate a net impact on the receiving water.
Attachment 2d	Geomorphic Assessment of Receiving Channels (Optional) See Section 6.3.4 of the Storm Water Design Manual.	□Not performed□Included□Submitted as separate standalone document
Attachment 2e	Vector Control Plan (Required when structural BMPs will not drain in 96 hours)	☐Included ☐Not required because BMPs will drain in less than 96 hours

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

PDP SWQMP - Attachments

This page was left intentionally blank.

Template Date: October 2016 PDP SWQMP - Attachments

Use this checklist to ensure the required information has been included on the Hydromodification Management Exhibit:

The Hydromodification Management Exhibit must identify:
□Underlying hydrologic soil group
☐ Approximate depth to groundwater
☐ Existing natural hydrologic features (watercourses, seeps, springs, wetlands)
☐ Critical coarse sediment yield areas to be protected
☐ Existing topography
☐ Existing and proposed site drainage network and connections to drainage offsite
□ Proposed grading
□ Proposed impervious features
□ Proposed design features and surface treatments used to minimize imperviousness
□ Point(s) of Compliance (POC) for Hydromodification Management
☐ Existing and proposed drainage boundary and drainage area to each POC (when necessary create separate exhibits for pre-development and post-project conditions)
Structural BMPs for hydromodification management (identify location, type of BMP, and
size/detail)

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

PDP SWQMP - Attachments

This page was left intentionally blank.

Template Date: October 2016 PDP SWQMP - Attachments

ATTACHMENT 3

Structural BMP Maintenance Information

This is the cover sheet for Attachment 3.

Indicate which Items are Included behind this cover sheet:

Attachment Sequence	Contents	Checklist
Attachment 3a	Structural BMP Maintenance Plan (Required)	□Included
		See Structural BMP Maintenance Information Checklist on the back of this Attachment cover sheet.
Attachment 3b	Draft Storm Water Control Facilities Maintenance Agreement (SWCFMA) (when applicable)	□Included □Not Applicable

Template Date: October 2016
PDP SWQMP - Attachments

This page was left intentionally blank.

Template Date: October 2016 PDP SWQMP - Attachments

Use this checklist to ensure the required information has been included in the Structural BMP Maintenance Information Attachment:

Attachment 3a must identify:

□ Specific maintenance indicators and actions for proposed structural BMP(s). This must be based on Section 7.7 of the Storm Water Design Manual and enhanced to reflect actual proposed components of the structural BMP(s)
☐ How to access the structural BMP(s) to inspect and perform maintenance
☐ Features that are provided to facilitate inspection (e.g., observation ports, cleanouts, silt posts, or other features that allow the inspector to view necessary components of the structural BMP and compare to maintenance thresholds)
☐ Manufacturer and part number for proprietary parts of structural BMP(s) when applicable
☐ Maintenance thresholds specific to the structural BMP(s), with a location-specific frame of reference (e.g., level of accumulated materials that triggers removal of the materials, to be identified based on viewing marks on silt posts or measured with a survey rod with respect to a fixed benchmark within the BMP)
□Recommended equipment to perform maintenance
☐When applicable, necessary special training or certification requirements for inspection and maintenance personnel such as confined space entry or hazardous waste management

Attachment 3b: For all Structural BMPs, Attachment 3b must include a draft maintenance agreement in the City's standard format (PDP applicant to contact City staff to obtain the current maintenance agreement forms or download from City's website).

Template Date: October 2016
PDP SWQMP - Attachments

This page was left intentionally blank.

Template Date: October 2016 PDP SWQMP - Attachments

ATTACHMENT 4

City of Escondido PDP Structural BMP Verification for Permitted Land
Development Projects

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

PDP SWQMP - Attachments

This page was left intentionally blank.

Template Date: October 2016 PDP SWQMP - Attachments

City of Escondido Storm Water Stru	uctural BMP Verification Form Page 1 of 4
Project Sum	nmary Information
Project Name	
Record ID (e.g., grading/improvement plan number)	
Project Address	
Assessor's Parcel Number(s) (APN(s))	
Project Watershed	
(Complete Hydrologic Unit, Area, and Subarea Name with Numeric Identifier)	
Maintenance Notification / Agreement No.	
Responsible Party	for Construction Phase
Developer's Name	
Address	
Email Address	
Phone Number	
Engineer of Work	
Engineer's Phone Number	
Responsible Party	for Ongoing Maintenance
Owner's Name(s)*	
Address	
Email Address	
Phone Number	
	ation for principal partner or Agent for Service of ne Board or property manager at time of project

Template Date: October 2016 PDP SWQMP - Attachments

City of Escondido Storm Water Structural BMP Verification Form Page 2 of 4 Stormwater Structural Pollutant Control & Hydromodification Control BMPs* (List all from SWQMP) Plan Maintenance Structural Description/Type of Revisions Sheet Agreement Structural BMP BMP ID# Recorded Doc # # *All Priority Development Projects (PDPs) require a Structural BMP

Note: If this is a partial verification of Structural BMPs, provide a list and map denoting Structural BMPs that have already been submitted, those for this submission, and those anticipated in future submissions.

Template Date: October 2016
PDP SWQMP - Attachments

City of Escondido Storm Structural BMP Verification Form Page 3 of 4

Checklist for Engineer of Work (EOW) to submit to Field Engineering:

 Copy of the final accepted SWQMP and any accepted Copy of the most current plan showing the Storm Water plans/cross-section sheets of the Structural BMPs and built Structural BMP. Photograph of each Structural BMP. Photograph(s) of each Structural BMP during the consproper construction. Copy of the approved Structural BMP maintenance agents. 	ter Structural BMP Table, d the location of each verified as-
By signing below, I certify that the Structural BMP(s) for this all BMPs are in substantial conformance with the approved understand the City reserves the right to inspect the above I approved plans and Storm Water Ordinance. Should it be constructed to plan or code, corrective actions may be neces Please sign your name and seal.	plans and applicable regulations. I BMPs to verify compliance with the letermined that the BMPs were not
Professional Engineer's Printed Name:	[SEAL]
Professional Engineer's Signed Name:	

City of Escondido Storm Water Structural BMP Verification Form Page 4 of 4

CITY - OFFICIAL USE ONLY: Permit #:_____ City Inspector: _____ Date Project has/expects to close: Date verification received from Engineer of Work (EOW): _____ By signing below, City Inspector concurs that every noted Structural BMP has been installed per plan. City Inspector's Signature: _____ Date: _____ FOR Environmental Programs: Date Received from Field Engineering: Environmental Programs Submittal Reviewer:_____ Environmental Programs Reviewer concurs that the information provided for the following Structural BMPs is acceptable to enter into the Structural BMP Maintenance verification inventory: List **acceptable** Structural BMPs:

Environmental Programs Reviewer's Signature:

Template Date: October 2016
PDP SWQMP - Attachments

Date:

ATTACHMENT 5

Copy of Plan Sheets Showing Permanent Storm Water BMPs, Source Control, and Site Design

This is the cover sheet for Attachment 5.

Use this checklist to ensure the required information has been included on the plans:

The plans must identify:
☐ Structural BMP(s) with ID numbers matching Step 6 Summary of PDP Structural BMPs ☐ The grading and drainage design shown on the plans must be consistent with the delineation
of DMAs shown on the DMA exhibit
□ Details and specifications for construction of structural BMP(s)
☐ Signage indicating the location and boundary of structural BMP(s) as required by City staff
☐ How to access the structural BMP(s) to inspect and perform maintenance
☐ Features that are provided to facilitate inspection (e.g., observation ports, cleanouts, silt posts, or other features that allow the inspector to view necessary components of the structural BMP and compare to maintenance thresholds)
☐ Manufacturer and part number for proprietary parts of structural BMP(s) when applicable
☐ Maintenance thresholds specific to the structural BMP(s), with a location-specific frame of reference (e.g., level of accumulated materials that triggers removal of the materials, to be identified based on viewing marks on silt posts or measured with a survey rod with respect to a fixed benchmark within the BMP)
□Recommended equipment to perform maintenance
☐When applicable, necessary special training or certification requirements for inspection and maintenance personnel such as confined space entry or hazardous waste management
□Include landscaping plan sheets showing vegetation requirements for vegetated structural BMP(s)
□All BMPs must be fully dimensioned on the plans
☐When proprietary BMPs are used, site-specific cross section with outflow, inflow, and model number must be provided. Photocopies of general brochures are not acceptable.
□Include all source control and site design measures described in Steps 4 and 5 of the SWQMP. Can be included as a separate exhibit as necessary.

*Note: Plan sheets included in this attachment can be full size or half size.

Template Date: October 2016 Preparation Date: [INSERT DATE OF SWQMP]

PDP SWQMP - Attachments