Utilities Approved Materials List - Potable Water/Recycled Water last updated 10/12/23

SIZE	DESCRIPTION	MANUFACTURER	NOTES	
	PIPE			
12" or smaller	North Americ	North American, Vinly Tech, Diamond PVC C-900		
14" or larger	US Pipe, Ame	rican DIP, McWayne Pipe	CMLC steel or Ductile Iron	
	CORPORATIO	N STOPS		
1" AND 2"	MIP X COMPRESSION BALL CORP STOP	FORD AY MCDONALD JONES MUELLER	QUICK JOINT COMPRESSION RING	
1" AND 2"	MIP X MIP BALL CORP STOP	FORD AY MCDONALD JONES MUELLER		
	ANGLE METE	R STOPS		
3/4" AND 1"	COMPRESSION X METER SWIVEL BALL ANGLE METER STOP	FORD AY MCDONALD JONES MUELLER	QUICK JOINT COMPRESSION RING 1" COMP X 3/4" METER NUT 1" COMP X 1" METER NUT	
1-1/2" AND 2"	COMPRESSION X FLANGE BALL ANGLE METER STOP	FORD AY MCDONALD JONES MUELLER	QUICK JOINT COMPRESSION RING 2" COMP X 1-1/2" FLANGE 2" COMP X 2" FLANGE	
SADDLES & TAPPING SLEEVES				
1" AND 2" SADDLES WITH FIP THREADS	ACP, DIP, & C-900	FORD AY MCDONALD JONES MUELLER	BRASS SADDLE WITH DOUBLE BAND STAINLESS STEEL STRAP SADDLE USED BASED ON SYSTEM PRESSURE (FOR C900, AC AND DIP). BRASS SADDLE W/DOUBLE BAND BRASS STRAP FOR AC AND DIP.	

Utilities Approved Materials List - Potable Water/Recycled Water last updated 10/12/23

	SADDLES & TAPPING	G SLEEVES CONTINUED	
3" AND ABOVE TAPPING SLEEN WITH FLANGE	/ES ACP, DIP, & C-900	POWER SEAL, ROMAC, JCM, SMITH BLAIR, FORD	NO RUBBER GASKETS ON FLANGE. MUST INCLUDE TEST PORT AND PLUG FOR PRESSURE TEST
	COU	I IPLINGS	
1" AND 2"	COMPRESSION X COMPRESSION MIP X COMPRESSION FIPXCOMPRESSION	FORD AY MCDONALD JONES MUELLER	USED ON COPPER TUBBING WHERE SHOWN OR APPROVED BY WATER DEPARTMENT ONLY
1" AND 2"	1" SWEAT X MALE SWEAT X SWEAT 1"SWEAT X MALE 2"SWEAT X SWEAT 2"SWEAT X SWEAT 90 ELL	·	USED ON COPPER TUBBING WHERE SHOWN OR APPROVED BY WATER DEPARTMENT ONLY
1" AND 2"	BRASS FIP X FIP		USED ON BRASS NIPPLES WHERE SHOWN OR APPROVED BY WATER DEPARTMENT ONLY
4" AND ABOVE	REPAIR, TRANSITION, CLOSURE	ROMAC 501 EPOXY COATED SS TRIM ROMAC MACRO EPOXY COATED SS TRIM SMITH BLAIR EPOXY COATED	ACP, DIP, PVC, STEEL WHERE SHOWN OR APPROVED BY WATER DEPARTMENT ONLY
4" AND ABOVE	FLANGE COUPLING ADAPTER FCA	ROMAC 501 EPOXY COATED SS TRIM	ACP WHERE SHOWN OR APPROVED BY WATER DEPARTMENT ONLY
4" AND ABOVE	REPAIR COUPLINGS PVC (C-900)		C-900 WHERE SHOWN OR APPROVED BY WATER DEPARTMENT ONLY

Utilities Approved Materials List - Potable Water/Recycled Water last updated 10/12/23

COPPER TUBING			
1" AND 2"	TYPE "K" SOFT		1" ROLLED TUBING (SOLDER ON COUPLING ONLY ON SERVICES LONGER THAN 100' 2" SERVICES, SOLDER AT 20' AND 90 DEGREE ELL
SILVER SOLDER	15%		
	SMALL FITT	INGS	
1" AND 2"	BRASS FITTINGS ONLY		VARYING SIZES AND CONFIGURATIONS
	VALVES	5	
3"-12"	GATE VALVE: RESILIENT WEDGE, NON RISING STEM, FLANGE BY FLANGE HOLIDAY FREE	1	TO CONFORM TO LATEST AWWA C- 509 SPECIFICATIONS. ALL STAINLESS STEEL TRIM
14"-20"	BUTTERFLY VALVE: MDT WITH BURIED SERVICE NUT HOLIDAY FREE	MUELLER PRATT	TO CONFORM TO LATEST AWWA C- 504 SPECIFICATIONS. ALL STAINLESS STEEL TRIM CLASS 150B
24" AND ABOVE	BUTTERFLY VALVE: MDT WITH BURIED SERVICE NUT HOLIDAY FREE	MUELLER PRATT	TO CONFORM TO LATEST AWWA C- 504 SPECIFICATIONS. ALL STAINLESS STEEL TRIM CLASS 150B

Utilities Approved Materials List - Potable Water/Recycled Water last updated 10/12/23

	COMBINATION AIR AND	VACUUM VALVES		
1" AND 2"	COMBINATION AIR RELEASE VACUUM VALVE	1" CLA-VAL (1-33 AKCX) 2" CLA-VAL (2-33 AKCX) 1" ARI D-040 2" ARI D-040 (ARI by Dept. approval only for low pressure areas)	EPOXY COATED (CLA-VAL BLUE)ALL STAINLESS STEEL	
4" AND 6"	COMBINATION AIR RELEASE VACUUM VALVE	4" APCO (149C) 6" APCO (151C) CLA-VAL 4" ARI D-060 6" ARI D-060 (ARI by Dept. approval only for low pressure zones) 4" CLA-VAL 33A FLG 6" CLA-VAL 33A FLG	EPOXY COATED -ALL STAINLESS STEEL	
	AUTOMATIC CONT	ROL VALVES		
2" AND ABOVE	AUTOMATIC PRESSURE REGULATING VALVE	CLA-VAL ALL STAINLESS STEEL TRIM	EPOXY COATED (CLA-VAL BLUE)ALL STAINLESS STEEL TRIM FLANGED	
	FIRE HYDRANTS			
RESIDENTIAL	ONE 4" AND ONE 2-1/2" OUTLETS	CLOW 850		
COMMERCIAL	TWO 4" AND ONE 2-1/2" OUTLETS	CLOW 865		
6" BURY ELL	PUSH-ON X FLANGE (C-900) FLANGE X FALNGE (STEEL & DI)		6 BOLT PATTERN	

Utilities Approved Materials List - Potable Water/Recycled Water last updated 10/12/23

	FIRE HYDRANTS C	CONTINUED	
6" SPOOLS	FLANGE X FLANGE VARYING SIZES		6 BOLT PATTERN NO BREAK-OFF SCORE
6" BREAK-OFF SPOOL	FLANGE X FLANGE		6 BOLT PATTERN BREAK-OFF SCORE
	METER BO	XES	•
3/4" AND 1" METER	#4-1/2 POLYMER CONCRETE BOX WITH READER LID #4-1/2 CONCRETE BOX WITH LID	J & R PROVIDED BY CITY	POLY BOX IN LANDSCAPED AREAS, CONCRETE BOX IN TRAFFIC AREAS RECYCLED WATER SERVICE LIDS TO READ "RECYCLED WATER"
1-1/2" AND 2" METER	#6B POLYMER CONCRETE BOX WITH READER LID	J & R PROVIDED BY CITY	POLY BOX IN LANDSCAPED AREAS, CONCRETE BOX IN TRAFFIC AREAS RECYCLED WATER SERVICE LIDS TO READ "RECYCLED WATER"
	PIPE FITTII	NGS	
4" AND LARGER	STEEL WELD, FLANGE X FLANGE, FLANGE X PUSH-ON, PUSH-ON X PUSH-ON, MECHANICAL JOINT, RESTRAINED MECHANICAL JOINT	TYLER, STAR (NO PUSH-ON)	ALL STAINLESS STEEL TRIM AND HARDWARE

Utilities Approved Materials List - Potable Water/Recycled Water last updated 10/12/23

DOMESTIC BACKFLOW PREVENTER			
3/4" - 2"	REDUCED PRESSURE PRINCIPLE BACKFLOW PREVENTER	WILKINS 975XL2, 375XL WATTS LF009-FS, LF919 AMES LF4000B FEBCO LF825Y, LF825YA	LEAD FREE DEVICES ONLY
2 1/2" - 10"	REDUCED PRESSURE PRINCIPLE BACKFLOW PREVENTER	WILKINS 375A, 475 WATTS 957-FS, 994-FS FEBCO LF860 AMES 4000SS-FS	LEAD FREE DEVICES ONLY
	FIRE DETECTOR CHE	· · · · · · · · · · · · · · · · · · ·	
4"-10"	VALVES MUST BE OS&Y - STYLE OF ASSEMBLY CAN VARY PER AREA & APPLICATION	(USC APPROVED ASSEMBLY) ZURN 375DA, 475DA WATTS LF957RPDA-FS FEBCO LF886V-FS AMES LFC500-FS, LFM500 DERINGER 50GX, 50G  (3/4" WATER METER MUST BE PURCHASED FROM THE CITY OF ESCONDIDO)	(RPDA) REDUCED PRESSURE DETECTOR ASSEMBLY



# City of Escondido Utilities Approved Materials List - Wastewater last updated 10/2023

Materials	Manufacturer (Series/Model	Additional Requirements/Comments
		PVC - SDR 35 (C-905 shall be used on force mains
Piping 18" and smaller		and in easements)
Piping Larger than 18"		High Density Polyethylene or C-900 for trunks
	Mission Flex-Seal Adjustable Repair Coupling	
Repair or Transition Couplings	(MR01) Fernco Strong Back Series	
Manhole Lining	Raven 405	
Sewer Lateral connections to main	Inserta Tee or SDR 35 wye	
	1" Combination Air Valve: APCO Model	
	443 2" Combination Air Valve: APCO	
	Model 445 4" Combination Air Valve:	
	APCO Model 449 6" Combination Air	
Air/Vacuum Release Valves	Valve: APCO Model 456 ARI (Model D-	
	020/D-025) (stainless steel only)	
Manhole frame & covers	Titus Twist Lock Composite	
	South Bay Foundry 24" cast iron	
Mainling Lines	Deline America CIDD	
Mainline Liner	Reline America CIPP	